

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

SECTION 1 - PRODUCT AND COMPANY INFORMATION

Product Number(s) BR1003, BR1003B, BR1003CN
 Product Name Moisture Displacing Fluid
 Synonyms None
 Products Uses Displaces moisture and prevents rust in gun bores

Revision No. 2
 Revision Date June 24, 2012
 Print Date June 24, 2012

| MANUFACTURER INFORMATION | | DISTRIBUTOR INFORMATION | |
|--------------------------|--------------------------------------|-------------------------|-------------------------------------|
| Company Name | Tri-Pac Inc | Company Name | Bushnell |
| Address | 17336 M-60 East Vandalia MI 49095 | Address | 9200 Cody Overland Park KC 66214 |
| Phone Number | 269-476-2303 | Phone Number | 800-423-3537 |
| Fax Number | 269-476-2302 | Fax Number | 913-752-3570 |

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION! AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. SKIN, EYE AND RESPIRATORY IRRITANT.

USA OSHA Classification This product is a "hazardous chemical" as defined by 29 CFR 1910.1200.
 European CLP Classification ACUTE TOX. 4, SKIN IRRIT. 2, EYE IRRIT. 2, MUTA. 1B, ASP. TOX. 1, AQUATIC CHRONIC 2.
 Canadian WHMIS Classification D1B, D2B – This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.
 HMIS III Classification Health: *2 Flammability: 1 Physical Hazard: 0
 NFPA Classification Health: 2 Flammability: 1 Reactivity: 0 Special Hazard: None

| HEALTH HAZARDS | | | | PHYSICAL HAZARDS | | | | | |
|-------------------|-------------------------------------|--------------|-------------------------------------|------------------------------|-------------------------------------|------------------|--------------------------|----------------|--------------------------|
| Irritant | <input checked="" type="checkbox"/> | Sensitizer | <input type="checkbox"/> | Flammable | <input type="checkbox"/> | Explosive | <input type="checkbox"/> | Pyrophoric | <input type="checkbox"/> |
| Acute Toxicity | <input checked="" type="checkbox"/> | Mutagenic | <input checked="" type="checkbox"/> | Under Pressure | <input type="checkbox"/> | Oxidizer | <input type="checkbox"/> | Water Reactive | <input type="checkbox"/> |
| Corrosive to Skin | <input type="checkbox"/> | Carcinogenic | SEE SECTION 11 | Self-Reactive | <input type="checkbox"/> | Organic Peroxide | <input type="checkbox"/> | Unstable | <input type="checkbox"/> |
| Target Organ SE | <input type="checkbox"/> | Reproductive | <input type="checkbox"/> | ENVIRONMENTAL HAZARDS | | | | | |
| Target Organ RE | <input type="checkbox"/> | Aspiration | <input checked="" type="checkbox"/> | Aquatic | <input checked="" type="checkbox"/> | Ozone Depleting | <input type="checkbox"/> | | <input type="checkbox"/> |

| UNITED STATES CPSC | USA / INTERNATIONAL GHS | CANADA WHMIS | CANADA CCCR |
|--|-------------------------|--------------|-------------|
| CAUTION EYE, SKIN, RESPIRATORY IRRITANT | | | |

POTENTIAL HEALTH EFFECTS AND SIGNS / SYMPTOMS OF EXPOSURE

Skin Contact Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.

Eye Contact Liquid contact may cause pain along with moderate eye irritation.

Ingestion May cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.

SAFETY DATA SHEET

24-hr Emergency Phone Number

800-255-3924 (Chem-Tel)

| | |
|--|--|
| Inhalation | <i>Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.</i> |
| Effects of Chronic Exposure | <i>Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal.</i> |
| Medical Conditions Aggravated | <i>May aggravate personnel with pre-existing disorders associated with any of the Target Organs.</i> |
| Target Organs | <i>Eyes, Skin, Respiratory System, Central Nervous System, Kidneys, Blood</i> |
| Routes of Exposure | <i>Skin Contact, Skin Absorption, Eye Contact, Inhalation, Ingestion</i> |
| Potential Environmental Effects | <i>See Section 12 for environmental effects</i> |

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| ID | INGREDIENT | CAS NUMBER | EINECS | EU CLASSIFICATION | % WT |
|----|---------------------------------|--------------|-----------|-------------------------------|-----------|
| 1 | Process Oil | 0064742-52-5 | 265-155-0 | | 30 - 60 |
| 2 | Stoddard Solvent | 0008052-41-3 | 232-489-3 | H340,H304 | 15 - 40 |
| 3 | 1,2,4-Trimethyl Benzene | 0000095-63-3 | 202-436-9 | H226,H332,H319,H335,H315,H411 | 7 - 13 |
| 4 | Castor Oil | 0008001-79-4 | 232-293-8 | | 7 - 13 |
| 5 | Light Aromatic Solvent Naphtha | 0064742-95-6 | 265-199-0 | H340,H304 | 3 - 7 |
| 6 | Sodium Sulfonate | 0068608-24-4 | 271-781-5 | | 3 - 7 |
| 7 | Isopropyl Benzene | 0000098-82-8 | 202-704-5 | H226,H304,H335,H411 | 0.5 - 1.5 |
| 8 | Ethylene Glycol Monobutyl Ether | 0000111-76-2 | 203-905-0 | H332,H312,H302,H319,H315 | 0.5 - 1.5 |
| 9 | Xylene | 0001330-20-7 | 215-535-7 | H226,H332,H312,H315 | 0.1 - 1.0 |
| 10 | Ethyl Benzene | 0000100-41-4 | 202-849-4 | H225,H332 | 0.1 - 1.0 |

| | |
|-------------------------------------|---|
| Hazard Statements | <i>See Section 15 for Hazard and Precautionary Statement text</i> |
| LD50 and LC50 Information | <i>See Section 11 for toxicological information</i> |
| Occupational Exposure Limits | <i>See Section 8 for OELs</i> |

SECTION 4 - FIRST AID MEASURES

| | |
|---------------------------|---|
| Ingestion | <i>DO NOT INDUCE VOMITING! ASPIRATION HAZARD! This material may enter the lungs during vomiting. Immediately have the victim drink plenty of water. Keep airways free. Contact a physician immediately. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.</i> |
| Skin Contact | <i>Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.</i> |
| Eye Contact | <i>Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.</i> |
| Inhalation | <i>Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.</i> |
| Notes to Physician | <i>Treat symptomatically.</i> |
| Antidotes | <i>No specific antidote.</i> |

SECTION 5 - FIRE FIGHTING MEASURES

| | |
|--|---|
| Flash Point | <i>304 °F (151.11 °C)</i> |
| Explosive Limits | <i>Not Available</i> |
| Autoignition Temperature | <i>Not Available</i> |
| Conditions of Flammability | <i>Heat, sparks, flame, red hot metal</i> |
| Extinguishing Media | <i>Water, CO₂, dry chemical, or universal aqueous film forming foam</i> |
| Unsuitable Extinguishing Media | <i>Water jet</i> |
| Hazardous Combustion Products | <i>Oxides of carbon (CO, CO₂), smoke, and vapors</i> |
| Sensitivity to Mechanical Impact | <i>Probably not sensitive as material is stable.</i> |
| Sensitivity to Static Discharge | <i>Vapor within the flammable limits may be ignited by a static discharge of sufficient energy.</i> |
| Special Equipment and Precautions | <i>Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure. Firemen should wear self-contained breathing apparatus.</i> |

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

Special Explosion Hazards *Not available*
Autoreactivity/Oxidizing Properties *Not available*

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions *Use personal protection recommended in Section 8. Isolate hazard area and deny entry to unnecessary and unprotected personnel.*

Environmental Precautions *Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.*

Containment Procedures *Released content may be contained with oil/solvent absorbent pads, booms, and/or other absorbents.*

Cleanup Procedures *Avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.*

Other Information *Consult the North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.*

Prohibited Materials *Combustible absorbent material such as sawdust, use of equipment that may cause sparking.*

Reporting Requirements *Report releases that reach surface water or groundwater in any amount. Reportable quantities for spills onto the ground depend on site conditions, such as the type of soil and type of material spilled. Federal and local agencies often have different reportable quantities.*

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling and Use *KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Always replace overcap when not in use. **Do not smoke** while handling or using this product. Avoid use around open flames or other sources of ignition. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.*

Storage Requirements and Conditions *Storage of individual cans should be done in an area below 120 °F (55 °C), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30 (Flammable and Combustible Liquids) is recommended and may be required by local and/or state law.*

Special Packaging Materials *Not applicable.*

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits

| ID | USA OSHA PEL | USA NIOSH REL | USA NIOSH IDLH | USA ACGIH TLV | AUSTRALIA TWA | GERMANY MAK | JAPAN OEL | ALBERTA CN OEL | BC CN TWA | ONTARIO CN TWAEV | QUEBEC CN TWA | MEXICO MPPEL-PTA | UK WEL |
|----|--------------|---------------------|-----------------------|---------------|-----------------------|-------------|---------------------|---------------------|-----------------------|-----------------------|---------------------|------------------|---------|
| 1 | N/E | N/E | N/E | N/E | 10 mg/m ³ | N/E | 3 mg/m ³ | 5 mg/m ³ | 1 mg/m ³ | 5 mg/m ³ | 5 mg/m ³ | N/E | N/E |
| 2 | 500 ppm | 20 g/m ³ | 350 mg/m ³ | 100 ppm | 790 mg/m ³ | N/E | N/E | 100 ppm | 290 mg/m ³ | 525 mg/m ³ | 100 ppm | 100 ppm | N/E |
| 3 | N/E | N/E | 25 ppm | 25 ppm | 25 ppm | 20 ppm | 25 ppm | 25 ppm | 25 ppm | 25 ppm | 25 ppm | 25 ppm | 25 ppm |
| 4 | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E |
| 5 | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E |
| 6 | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E | N/E |
| 7 | 50 ppm | 900 ppm | 50 ppm | 50 ppm | 25 ppm | 20 ppm | N/E | 50 ppm | 25 ppm | 50 ppm | 50 ppm | 50 ppm | 25 ppm |
| 8 | 50 ppm | 700 ppm | 5 ppm | 20 ppm | 20 ppm | 20 ppm | N/E | 25 ppm | 20 ppm | 20 ppm | 20 ppm | 20 ppm | 25 ppm |
| 9 | 100 ppm | 900 ppm | 100 ppm | 100 ppm | N/E | 100 ppm | 50 ppm | 100 ppm | 100 ppm | 100 ppm | 100 ppm | 100 ppm | 50 ppm |
| 10 | 100 ppm | 800 ppm | 100 ppm | 20 ppm | 100 ppm | 100 ppm | 50 ppm | 100 ppm | 100 ppm | 100 ppm | 100 ppm | 100 ppm | 100 ppm |

Biological Exposure Indices

| ID | DETERMINANT | SAMPLING TIME | BEI | NOTATION |
|----|---|---------------------------------|--------------------|----------|
| 9 | Methylhippuric acids in urine | End of shift | 1.5 g/g creatinine | |
| 10 | Sum of mandelic acid and phenyl glyoxylic acid in urine | End of shift at end of workweek | 0.7 g/g creatinine | Ns, Sq |

Engineering Measures *Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.*

General Hygiene Considerations *Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.*

Thermal Hazards *This product does not present a thermal hazard.*

Respiratory Protection *An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.*

SAFETY DATA SHEET

24-hr Emergency Phone Number

800-255-3924 (Chem-Tel)

| | |
|-----------------------------------|---|
| Skin Protection | <i>For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.</i> |
| Eye/Face Protection | <i>Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.</i> |
| Other Protective Equipment | <i>Safety showers and eye-wash stations should be available in the workplace near where the material will be used.</i> |

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------------------------|---------------------------|---------------------------------------|-----------------------------|
| Boiling Point | 300-500 °F (149-260 °C) | Melting / Freezing Point | Not Available |
| Flash Point | 304 °F (151 °C) | Autoignition Temperature | Not Available |
| Explosive Limits | Not Available | Density (H2O = 1) | 0.866 g/cc |
| Flammability | Class III Liquid | Weight | 7.228 lbs/gal |
| Molecular Weight | Not Available | pH | Not Available |
| Vapor Pressure | 1.5 mm Hg | Evaporation Rate | Not Available |
| Vapor Density | Not Available | Partition Coefficient | Not Available |
| Physical State | Liquid | Refractive Index | Not Available |
| Viscosity | Not Available | Heat of Combustion | Not Available |
| Odor | Characteristic | Water Solubility | Not Available |
| Appearance / Color | Clear light to dark amber | VOC Content | 3.360 lbs/gal (402.502 g/L) |
| Percent Volatile | 50% Wt (51% Vol) Max | HAP Content | 0.130 lbs/gal (15.569 g/L) |
| Percent VOC | 50% Wt (51% Vol) Max | Maximum Incremental Reactivity | 1.914 g O3/g |
| Solids/Non Volatile Content | 50% Wt (49% Vol) Max | | |

SECTION 10 - STABILITY AND REACTIVITY

| | | | |
|---------------------------------|--|------------------------------|-----------------------|
| Stability | Stable | Conditions to Avoid | Not Available |
| Physical Hazards | Not Available | Hazard Polymerization | Not expected to occur |
| Decomposition Products | Oxides of carbon | | |
| Conditions of Reactivity | Heat, sparks, flame, red hot metal | | |
| Material Incompatibility | Strong Oxidizing Agents, Acids, Bases, Perchloric And Permonosulfuric Acids, Nitric Acid, Dichlorohydrantion | | |

SECTION 11 - TOXICOLOGICAL INFORMATION

| | |
|---------------------------------|--|
| Irritancy of Product | <i>The following ingredients are skin irritants: Trimethyl Benzene, Ethylene Glycol Monobutyl Ether, Xylene. The following ingredients are eye irritants: Trimethyl Benzene, Ethylene Glycol Monobutyl Ether. The following ingredients are respiratory irritants: Trimethyl Benzene, Isopropyl Benzene.</i> |
| Sensitization to Product | <i>None of the ingredients are known or suspected sensitizers.</i> |
| Carcinogen Data | <i>[Isopropyl Benzene] is listed as follows: State of California on Prop-65. [Ethylene Glycol Monobutyl Ether] is listed as follows: ACGIH as A3 (confirmed animal carcinogen with unknown relevance to humans). [Ethyl Benzene] is listed as follows: State of California on Prop-65. ACGIH as A3 (confirmed animal carcinogen with unknown relevance to humans). IARC as Group 2B (possibly carcinogenic to humans).</i> |
| Reproductive Toxicity | <i>None of the ingredients are known or suspected reproductive toxins.</i> |
| Teratogenicity | <i>None of the ingredients are known or suspected teratogens.</i> |
| Mutagenicity | <i>The following ingredients are considered mutagens: Stoddard Solvent, Light Aromatic Solvent Naphtha</i> |
| Synergistic Products | <i>Not Available</i> |

LD50 and LC50 Information

| ID | ORAL LD50 | | DERMAL LD50 | | INHALATION LC50 | | |
|----|--------------|---------|--------------|---------|-----------------|------|---------|
| | VALUE | SPECIES | VALUE | SPECIES | VALUE | TIME | SPECIES |
| 1 | > 2000 mg/kg | rat | > 2000 mg/kg | rabbit | 5 mg/L | 4 hr | rat |
| 2 | | | 500 mg/kg | rabbit | | | |

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

| | | | | | | | |
|----|--------------|-----|--------------|--------|------------------------|------|-------|
| 3 | 5000 mg/kg | rat | > 3160 mg/kg | rabbit | 18 mg/L | 4 hr | rat |
| 5 | 4700 mg/kg | rat | 4000 mg/kg | rabbit | 3670 ppm | 8 hr | rat |
| 6 | > 5000 mg/kg | rat | | | | | |
| 7 | 2700 mg/kg | rat | > 3160 mg/kg | rabbit | 10 mg/L | 7 hr | mouse |
| 8 | 470 mg/kg | rat | 220 mg/kg | rabbit | 2211 mg/m ³ | 4 hr | rat |
| 9 | 2840 mg/kg | rat | 4500 mg/kg | rabbit | 6300 mg/L | 4 hr | rat |
| 10 | 3500 mg/kg | rat | 15500 mg/kg | rabbit | | | |

SECTION 12 - ECOLOGICAL INFORMATION

| | | | |
|-----------------------------------|---|------------------------|---------------|
| Mobility | Not Available | Degradability | Not Available |
| Persistence | Not Available | Bioaccumulation | Not Available |
| Other Ecologic Data | Do not allow to enter waters, waste water, or soil. This product is very toxic to aquatic life. | | |
| Effects on the Ozone Layer | This product does not contain any ozone depleting ingredients. | | |

Ecotoxicity

| ID | TYPE | FISH | | | INVERTEBRATES | | | AQUATIC PLANTS | | | MICROORGANISMS | | |
|----|------|-----------|--------|------|---------------|--------|------|----------------|--------|------|----------------|--------|--|
| | | VALUE | PERIOD | TYPE | VALUE | PERIOD | TYPE | VALUE | PERIOD | TYPE | VALUE | PERIOD | |
| 3 | LC50 | 7.72 mg/L | 96 hr | EC50 | 3.6 mg/L | 48 hr | | | | | | | |
| 5 | LC50 | 320 mg/L | 48 hr | EC50 | 170 mg/L | 24 hr | EC50 | 56 mg/L | 72 hr | | | | |
| 7 | LC50 | 4.7 mg/L | 96 hr | EC50 | 13.7 mg/L | 24 hr | EC50 | 26 mg/L | 72 hr | EC10 | 211 mg/L | 24 hr | |
| 8 | LC50 | 1490 mg/L | 96 hr | EC50 | 1720 mg/L | 24 hr | LOEC | 900 mg/L | 7 day | EC5 | 911 mg/L | 48 hr | |
| 9 | LC50 | 26.7 mg/L | 96 hr | EC50 | 14 mg/L | 24 hr | | | | | | | |
| 10 | LC50 | 12.1 mg/L | 96 hr | LC50 | 77 mg/L | 24 hr | EC50 | 63 mg/L | 3 hr | EC50 | 160 mg/L | 96 hr | |

SECTION 13 - DISPOSAL CONSIDERATIONS

| | |
|------------------------------------|---|
| Waste Disposal | Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations. |
| Waste Disposal of Packaging | Consult with your local landfill to determine if empty small containers can be disposed of in regular trash pickup. For disposal of large containers, or for containers not suitable for landfill, a licensed reconditioner should be used. |
| Landfill Precautions | Not Available |
| Incineration Precautions | Not Available |

SECTION 14 - TRANSPORTATION INFORMATION

NON-REGULATED MATERIAL

SECTION 15 - REGULATORY INFORMATION

UNITED STATES - FEDERAL

| ID | TSCA | SARA 302 | RCRA | CERCLA | SARA 313 | FIRE | REACTIVITY | SARA 311/312 | | PRESSURE | CLEAN AIR ACT | | CLEAN WATER ACT |
|----|-----------|----------|------|--------|----------|------|------------|--------------|---------|----------|---------------|-------|-----------------|
| | INVENTORY | EHS | | | | | | ACUTE | CHRONIC | | HAP | SOCMI | |
| 1 | ✓ | | | | | | | | | | | | |
| 2 | ✓ | | | | | | | | | | | | |
| 3 | ✓ | | | | 10 % | Yes | | Yes | | | | | |
| 4 | ✓ | | | | | | | | | | | | |
| 5 | ✓ | | | | | | | | | | | | |
| 6 | ✓ | | | | | | | | | | | | |
| 7 | ✓ | | U055 | 5000 | 1 % | Yes | | | Yes | | Yes | Yes | |
| 8 | ✓ | | | | | | | Yes | Yes | | | | |
| 9 | ✓ | | U239 | 100 | < 1 % | Yes | | Yes | Yes | | Yes | Yes | 100 |
| 10 | ✓ | | | 1000 | < 1 % | Yes | | Yes | Yes | | Yes | Yes | 1000 |

SAFETY DATA SHEET

24-hr Emergency Phone Number
800-255-3924 (Chem-Tel)

UNITED STATES - STATES

| ID | CA PROP 65 | DE DRQ | MA RTK CODES | ME TYPE | ME RQ | MN HAZ CODE | NJ RTK | NY AIR RQ | NY LAND RQ | NY ACUTE | PA HAZ CODE | WA PEL TWA |
|----|---------------|-----------|------------------|------------|----------|----------------|-----------|--------------|---------------|-------------|----------------|---------------|
| 1 | | | | | | | | | | | | |
| 2 | | | 2,4 | | | ANO | | | | | Yes | 100 ppm |
| 3 | | 100 | F7 F9 | | 1000 | | Yes | | | | Yes-E | |
| 4 | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | |
| 7 | C | 500 | 2,4,5 F7 F8 F9 | | 2000 | AO | Yes | | 5000 | 1 | Yes-E | |
| 8 | | | 2,4,6 F8 | | | AO | | | | | Yes | |
| 9 | | 100 | 2,4 F8 F9 | | 2000 | ANO | Yes | | 1000 | 1 | Yes-E | |
| 10 | C | 1000 | 2,4,5,6 F7 F8 F9 | | 2000 | AO | Yes | Yes | 1000 | 1 | Yes-E | |

CANADA

| ID | WHMIS CATEGORIES | | | | | | | | | | CHEMICAL LISTS | | |
|----|------------------|----|---|-----|-----|-----|-----|----|---|-----|----------------|-------|-----|
| | A | B | C | D1A | D1B | D2A | D2B | D3 | E | DSL | NDSL | NPRI | CWC |
| 1 | | | | | | | | | | ✓ | | | |
| 2 | | B3 | | | | | ✓ | | | ✓ | | 5 | |
| 3 | | B3 | | | | | | | | ✓ | | 1A, 5 | |
| 4 | | | | | | | | | | ✓ | | | |
| 5 | | B3 | | | | | ✓ | | | ✓ | | 5 | |
| 6 | | | | | | | | | | ✓ | | | |
| 7 | | B2 | | | | ✓ | | | | ✓ | | 1A | |
| 8 | | B3 | | ✓ | | | ✓ | | | ✓ | | 1A, 5 | |
| 9 | | B2 | | | | ✓ | ✓ | | | ✓ | | 1A, 5 | |
| 10 | | B2 | | | | ✓ | ✓ | | | ✓ | | 1A | |

EUROPEAN UNION

| CODE | HAZARD STATEMENTS |
|------|---|
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H340 | May cause genetic defects |
| H411 | Toxic to aquatic life with long lasting effects |

| CODE | PRECAUTIONARY STATEMENTS |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. |
| P306+P360 | IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention |
| P309+P311 | IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. |
| P330 | Rinse mouth. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P334 | Immerse in cool water/wrap in wet bandages. |
| P338 | Remove contact lenses, if present and easy to do. Continue rinsing. |
| P342 | If experiencing respiratory symptoms: remove to fresh air |
| P350 | Gently wash with plenty of soap and water. |
| P353 | Rinse skin with water/shower. |
| P370+P378 | In case of fire: Use dry chemical extinguishers for extinction. |
| P381 | Eliminate all ignition sources if safe to do so. |
| P403 | Store in a well-ventilated place. |

AUSTRALIA

Poisons Schedule Number None of the ingredients are present at or above a concentration necessary for allocation of a Poisons Schedule Number.

Chemical Inventory Status All of the ingredients are listed on the Australian Inventory of Chemical Substances (AICS) or are exempt.

SAFETY DATA SHEET

24-hr Emergency Phone Number

800-255-3924 (Chem-Tel)

SECTION 16 - OTHER INFORMATION

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

Revision History

Revision 1, 10/27/2010, Original

Revision 2, 06/24/2012, Total revision with new shipping, GHS, and CLP information